




A Unique Design...

External layer of ORCA® Chlorosulfonated Polyethylene (CSM) gives:

- Weatherproof resistance (fading and aging)
- Chemical resistance
- Abrasion resistance

Interlayer Neoprene® (CR) between the CSM and textiles gives:

- Optimal adhesion to textile and rubber



Neoprene inner layers gives:

- Perfect air & water tightness
- Excellent adhesion to textile and rubber

...For Exceptional Properties

Resistance

- To hydrocarbons
- To abrasion and tear
- To ozone & ultraviolet

Longevity

- Durable gluing
- Perfect air & water tightness
- Resistance to extreme temperatures

Design

- Color resistant
- Suppleness
- Esthetics & texture

HIGH TENACITY FABRIC:

- Excellent mechanical properties
- Tensile strength and high tear
- Excellent dimensional stability


ORCA Fabrics
WARRANTY
5 years



Pennel & Flipo Europe

Boulevard de l'Eurozone 102 - 7700 Mouscron - Belgique

e-mail : info@orca.eu - Tél. +32 56 39 21 00





Our ORCA® Fabric

A wide range of fabrics adapted to every type of boat

ORCA® for Inflatable Tubes

Depending on boat size and application, the manufacturer has a choice of fabrics ranging from 800 g / m² and 2200 g / m². Our current fabrics support loads of 275 kg / 5 cm to 1 200 kg / 5 cm.

- ORCA® 215 - PES 1100 dtex Textile - 880 g/m²
- ORCA® 820 - PES 1100 dtex Textile - 1050 g/m²
- ORCA® 828 - PES 1100 dtex Textile - 1300 g/m²
- ORCA® 866 - PES 1670 dtex Textile - 1500 g/m²
- ORCA® 866S - PA 1880 dtex Textile - 2210 g/m²

ORCA® for Internal Tape and Baffle

- ORCA® 861 663
- ORCA® 861 664
- ORCA® 861 665
- ORCA® 861 TAPE



A wide range of accessories:

- ORCA® Glue
- ORCA® Rubrail
- ORCA® Cleaners
- Nauta® Flexible Tanks

Pennel & Flipo Europe

Boulevard de l'Eurozone 102 - 7700 Mouscron - Belgique
e-mail : info@orca.eu - Tél. +32 56 39 21 00